



PIN ASSIGNMENT

POS. NO.	T568B WIRING (PC TO HUB)	POS. NO.
1	ORANGE	1
2	WHITE/ORANGE	2
3	GREEN	3
6	WHITE/GREEN	6
4	WHITE/BLUE	4
5	BLUE	5
7	BROWN	7
8	WHITE/BROWN	8
SHELL	SHIELD	SHELL

	OPERATING TEMP.	-20°C - +60°C
3	OVER MOLD	PVC 7&P OVERMOLD COLOR: BLACK
2	PLUG	RJ45 8P&C MODULAR PLUG
1	CABLE	CAT.6 SHIELDED 26AWG STRANDED PATCH CORD JACKET: PVC. COLOR: BLACK
NO.	ITEM	DESCRIPTION

*PLEASE NOTE: LAST 4 DIGITS DENOTES LENGTH IN FEET
I.E. J2060-0003 = 3' CABLE

REVISION					
REV	DESCRIPTION	EDD No.	CHG. BY	DATE	APPROVED
1					
2					
3					

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN FEET.
CABLE LENGTH TOLERANCES:

XXXX ≤ 1 ft	±1 inch, 0 inch
XXXX > 1 ft to 5 ft	±2 inches, 0 inch
XXXX > 5 ft to 10 ft	±4 inches, 0 inch
XXXX > 10 ft to 25 ft	±8 inches, 0 inch
XXXX > 25 ft	±1%, 0%

THIS DOCUMENT IS THE
CONFIDENTIAL PROPERTY OF
JEM ELECTRONICS, INC. AND
SHALL NOT BE USED IN ANY WAY
WITHOUT THE CONSENT OF
JEM ELECTRONICS, INC.

JEM ELECTRONICS, INC.
23 NATIONAL DRIVE, FRANKLIN, MA 02038

ISSUING NAME
CAT 6 SHIELDED RED PATCH CORD

THIRD ANGLE PROJECTION

DRAWING NO. **J2060-XXXX** Rev.
SCALE 1:1 10/27/10 SHEET: 1 OF 1